



**PLAST**  
*www.miko-plast.com*

Østre Aker Vei 22, N-0581 OSLO, NORWAY

TELEPHONE : + 47 23 38 47 73  
ENTERPRISE NO: 980 030 628

**Miko Core Plug 71,6™**

**Doc.7:4**

**PRODUCT DATA :**

Core Ø.....	71,6 mm
Dimension insertion angle .....	64-70 mm
Dimension .....	70-71,6 x 30 x 25 mm
Dimension lock ribs .....	72, 5 mm
Tolerance.....	+ - 0,3 mm
Weight.....	36,0 gram
Material .....	PEHD
Alternative material.....	PP
Compression strength deformation .....	4 KN
Compression strength break.....	8 KN
Tolerance.....	1 KN

**PACKAGING:**

Packing.....	Octabin
Number each packing.....	8.000 stk.
Netto weight each packing .....	280 kg

**MATERIAL RECYCLING DATA HDPE:**

Density	ISO1183 .....	962 kg/m <sup>3</sup>
Melt index 190°C/2,16 kg	ISO 1133.....	12 g/10min
Tensile strength	ISO 527-2 .....	1150 Mpa
Surface hardness	ISO 868.....	62 Shore D
Heat deflection	ISO 75-2 .....	73°C
Impact strength	ISO 8256*/A1 .....	50 KJ/m <sup>2</sup>