



PLAST
www.miko-plast.com

Østre Aker Vei 22, N-0581 OSLO, NORWAY

TELEPHONE : + 47 23 38 47 73
ENTERPRISE NO: 980 030 628

Miko Core Plug 72™

Doc.7:5

PRODUCT DATA:

| | |
|--|--------------------|
| Core Ø | 72 mm |
| Dimension insertion angle..... | 64-71 mm |
| Dimension | 71-72 x 27 x 25 mm |
| Dimension lock ribs | 73 mm |
| Tolerance..... | + - 0, 50 mm |
| Weight | 32 gram |
| Material | PEHD |
| Alternative material..... | PP |
| Compression strength deformation | 4 KN |
| Compression strength break | 8 KN |
| Tolerance..... | 1 KN |

PACKAGING:

| | |
|-------------------------------|------------|
| Packing..... | Octabin |
| Number each packing..... | 8.000 pcs. |
| Net weight each packing | 256 kg |

MATERIAL RECYCLING DATA HDPE:

| | | |
|--------------------------|--------------------|------------|
| Density | ISO1183 | 962 kg/m3 |
| Melt index 190°C/2,16 kg | ISO 1133..... | 12 g/10min |
| Tensile strength | ISO 527-2 | 1150 Mpa |
| Surface hardness | ISO 868..... | 62 Shore D |
| Heat deflection | ISO 75-2 | 73°C |
| Impact strength | ISO 8256*/A1 | 50 KJ/m2 |